

VELOCITY GX9

PRODUCT DESCRIPTION:

VELOCITY GX 9 is formulated with a proprietary mixture of premium and super premium quality base oils with an additive technology delivering very high performance and engine protection under a variety of driving conditions. It meets the most difficult conditions of use (motorway, heavy urban traffic, etc.) during all seasons.

APPLICATION:

Naturally aspirated and turbocharged gasoline engines in passenger cars and light commercial vehicles. Four stroke gasoline engines and portable power equipment.

FEATURES & BENEFITS:

- Very good low temperature properties
- Protection to wear by cold start
- Very high thermal and oxidation stability
- Excellent resistance against foaming, corrosion and wear
- High dispersancy and detergency level
- High viscosity index

PERFORMANCE LEVELS: Meets and Exceeds:

- API Service Category SL/CF
- ACEA A3/B3, A3/B4
- VW 502 00 / 505 00
- MB 229.3 / 229.1
- RN 700, RN 710

API LICENSE:

- SAE 10W-30
- SAE 10W-40



TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	VELOCITY GX9	
Grade			10W30	10W40
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	77.45	100.5
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	12.0	15.0
Viscosity Index (min)	ASTM D-2270	-	151	157
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm ³	0.869	0.870
Flash Point (min)	ASTM D-92	°C	230	230
Pour Point (max)	ASTM D-97	°C	-36	-36
TBN	ASTM D-2896	Mg KOH/g	8	8
CCS, (°C)	ASTM D-5293	m.Pa.S	6400 (-25)	6500 (-25)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net